
CS 537 Lecture 21A Virtual Machines

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller



Virtual Machines



A thin software layer that sits between Intel hardware and the operating system virtualizing and managing all hardware resources

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller

Virtual Machine Monitors

- A VMM implements the hardware interface in software
 - All instructions that reference privileged processor state refer to a software copy
 - All instructions that refer to specific physical resources (e.g., memory pages) refer to virtual resources selected by the VMM
 - All commands/instructions that refer to specific physical devices refer to software that implements/emulates that device interface
 - All interrupts from physical devices are handled by VMM
 - VMM must be at higher privilege level than guest VM, which generally runs in user mode

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller

Virtual Machine Monitors (VMMs)

- A Virtual Machine is a software version of the hardware state of a computer system
 - An operating system running within a virtual machine is called a guest operating system
- Virtual machine monitor (VMM) or hypervisor is software that implements and supports VMs
 - VMM determines how to map virtual resources to physical ones
 - Physical resource may be time-shared, partitioned, or emulated in software
 - VMM much smaller than a traditional OS;
 - Isolation portion of a VMM is \approx 10,000 lines of code

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller

Why use VMMs

- · Add features hard to do in an OS
 - Suspend/resume: save state to disk and reload
 - Migration: save state to network file system, reload on another machine
- Share hardware
 - Consolidate multiple services from different slow machines
- · Security/isolation
 - Share a single web server with multiple customers (e.g., Amazon EC2)
 - Each virtual host gets its own adminstrator/root.
- Run applications for another OS
 - Run Windows apps in a virtual machine on MacOS

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea. Michael Swift, Barton Miller

Implementation Issues

- Who provides the resource management serves for the VMM?
 - another OS
 - the VMM itself
- · What hardware does the VMM expose?
 - The same as a physical machine?
 - Something simpler?
- How are privileged operations performed?

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller

Virtual Machine Types


- Type 1 / Type 2
 - Type 1 VMMs (called Hypervisors) sit just above the HW and virtualize the complete hardware
 - Example: VM/360, Xen, VMware ESX server
 - Type 2 VMMs run within an OS, and rely on OS services to manage HW
 - Example: QEMU, VMware Worksation, Mac Parallels


4/11/2011

7

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller

8






Comparison

- Type 1 (native)
 - All OS's on the machine more slowly
 - All drivers run in the VMM (VMware) or a special guest OS (Xen)
 - System management is done in a guest OS
- Type 2 (hosted)
 - Host OS runs full speed, guests more slowly
 - All drivers run in host OS, leverage large code base
 - System management is done in host OS

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller 11



Virtualization Technology

- · Basic approach: execute privileged software at unprivileged level
 - Privileged instructions will trap: I/O, memmgmt
 - Emulate behavior of privileged instructions in software in
- · VMM has complete control over the HW
 - Presents another layer of virtual memory under the OS with a separate page table
 - Presents a different set of devices to the OS
- · What happens to instructions that return different results in priv. mode and normal mode?

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller

13

15

ISA Impact on Virtual Machines

- Consider x86 PUSHF/POPF instructions
 - Push flags register on stack or pop it back
 - Flags contains condition codes (good to be able to save/restore) but also interrupt enable flag (IF)
- · Pushing flags isn't privileged
 - Thus, guest OS can read IF and discover it's not the way it was set
 - · VMM isn't invisible any more
- Popping flags in user mode ignores IF
 - VMM now doesn't know what guest wants IF to be
 - Should trap to VMM
- Possible solution: modify code, replacing pushf/popf with special interrupting instructions
 - But now guest can read own code and detect VMM

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller

14

16

Classification of processor architectures

- · Strictly virtualizable processor architectures
 - Can build a VMM based on trap emulation exclusively
 - No software running inside the VM cannot determine the presence of the VMM (short of timing attacks)
 - Examples: IBM S/390, DEC Compaq Intel Alpha, PowerPC (Non-strictly) virtualizable prosessor architectures
- - Trap emulation alone is not sufficient and/or not complete
 - E.g. instructions have different semantics at various levels (sufficient)
 - E.g Some software sequences can determine the presence of the VMM (complete)
 - Examples: IA-32, IA-64
- Non virtualizable processor architectures
 - Basic component missing (e.g. MMU, ...)

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller

Virtualizing x86

- · Pure approaches:
 - systems present the interface of real, existing HW and can run unmodified operating systems
 - Binary translation
 - · Convert kernel code into a new binary that calls into VMM for all privileged instructions / instructions that do something different between kernel/user mode (VMware)
 - Emulation
 - Emulate all instructions in kernel mode (VirtualPC)
- New hardware
 - Intel VT, AMD Pacifica adds new ring (-1) that traps correctly

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller

Para-Virtualization

- · Para-virtualize side steps the problem
 - present a new, simpler interface but require OS modifications
 - Change kernel code to avoid all privileged instructions
 - Issue explicit HyperCalls into VMM to provide these
- · Made possible when:
 - Operating system source is available
 - . Open source: Linux and Xen
 - OS vendor writes VMM: Microsoft Windows/HyperV, Sun Solaris LDOM, IBM AIX/LPAR

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller

17


Virtualizing Memory


- · VMMs present virtual memory to an OS as physical memory
 - Allows the VMM to reclaim pages, swap, give to another VM
- · use 3 layer translation: virtual, real, physical
 - OS manages Virtual -> real translation with existing page
 - VMM manages real -> physical translation
- - Trap-on-write to OS page table
 - Shadow page table given to hardware that maps virtual -> physical directly

4/11/2011


© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller

18





Virtualizing Devices Virtualization by Emulation Trap on read/write of device registers Emulate device action in VMM Virtualization by Replacement Write a new driver for the class of device (e.g., network) Network driver explicitly calls into VMM to perform work VIII and Provided Self-Lazzoska, Hark Ley, Andrea and Rend Appel-Chasse, Midwal Self-Lazzoska, Hark Ley, Andrea and Rend Apple Chasse, Midwal Self-Lazzoska, Bark Ley, Andrea and Rend Apple Chasse, Midwal Self-Lazzoska, Bark Ley, Andrea and Rend Apple Chasse, Rend Ley, Andrea and Rend Apple Chas



Virtualizing Disks

- Sharing
 - Networking shared a single device through time multiplexing
 - Disks share through space multiplexing
 - Some device might not be shared, but just assigned to a single VMM, which can run the driver itself
 - USB flash drive
- VMM makes a file in the FS act like a disk to the VMM
 - Can grow incrementally as disk is used
 - Can be copied between systems
- Done by implementing a SCSI or IDE device that talks to the FS

4/11/2011

© 2004-2011 Ed Lazowska, Hank Levy, Andrea and Remzi Arpaci-Dussea, Michael Swift, Barton Miller 23